ThinkStation P520c 30BX000MGE

Region
WE

Country
Germany

Machine Type
30BX

TopSeller
TopSeller

Processor
Xeon W-2123 4C/3.6GHz/8.25MB/120W/DDR4-2666

Memory
1x 16GB RDIMM DDR4-2666 ECC

Discrete Graphics Card
Open

Monitor Cable
None

Storage Controller
Integrated Intel SATA

Internal Disks
1x 256GB SSD 2.5" SATA6Gbps Opal

Disks in Flex Bay
None

Flex Bay
None

M.2 RAID
None

M.2 Drives - Onboard
None

M.2 Drives - via Single M.2 PCIe adapter
None

M.2 Drives - Front Removable
None

PCIe SSD Adapter
None

Optical
1x HH DVD±RW

WLAN + Bluetooth
None

Media Reader
9-in-1

Available Networking Ports
1x GbE

Chassis Intrusion Switch
Chassis Intrusion Switch

Front Diagnostic LED
None

System Management
ThinkStation P520c

Thunderbolt Ports
None

USB Type-C Ports
None

Optionl Legacy Ports (COM/1394/eSATA/Parallel)
1x COM (Rear)

Internal USB
None

Power Supply
Fixed 500W Platinum

Keyboard
USB Full

Mouse
USB Optical

Operating System
Windows 10 Pro 64 for Workstations

Warranty
3-year, Onsite

Global
No

End of Support
2024/02/25

Ann Date
2018/01/25

Note:

* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries

WWW.LENOVO.COM

This publication was developed for products and services oered in the United States and E.M.E.A countries. Lenovo may not oer the products, services or features discussed in this document in other countries. Lenovo may withdraw an oering at any time. Information is subject to change without notice. Consult your local representative for information on oerings available in your area.

Lenovo reserves the right to change specifcations or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication “as is” without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.

http://psref.lenovo.com

Visit psref website for the latest version of Product Specifcations Reference.

© Lenovo, 2017. All rights reserved.

ThinkStation P520c Platform Specifications

Components	Specification
Form factor	25L Tower
Dimensions	175mm/6.89" W x 426mm/16.77" D x 376mm/14.8" H (with feet)
Weight	Maximum configuration: 31.97 lb (14.5kg)
Processor	Up to one 140W Intel Xeon W family processor. Up to 18 cores at 2.3GHz, up to 4.0GHz with 4 cores. Memory speed up to DDR4-2666
Chipset	Intel C422 Chipset
Memory	4 DIMM sockets with 4 channels. RDIMMs. DDR4-2666
Memory capacity	Up to 128GB with 4 x 32GB RDIMMs
Memory protection	ECC
Graphics	Two PCIe 3.0 x16 slots (see Expansion slots section). Up to one NVIDIA Quadro P5000 plus one Quadro P2000, or up to two Quadro P4000. Other graphics adapters under 75W up to 2. Supports the following graphics adapters:

Adapter	Cores	Memory	Power	Connector	SLI
NVS 310	48	1GB	19.5W	2xDP	
NVS 315	48	1GB	19.3W	2xDVI-I SL/2xDP	
NVS 510	192	2GB	33.4W	4xmini DP	
NVS 810	1024	4GB	68W	8xmini DP	
Quadro P400	256	2GB	30W	3xminiDP	
Quadro P600	384	2GB	45W	4xminiDP	
Quadro P620	512	2GB GDDR5	40W	4x miniDP	
Quadro P1000	640	4GB	50W	4xminiDP	
Quadro P2000	1024	5GB	75W	4xDP	
Quadro P4000	1792	8GB	120W	4xDP	
Quadro P5000	2560	16GB	180W	DVI-D DL+4xDP	

Storage controllers	Integrated Intel SATA AHCI/RAID controller in chipset, 6Gbps SATA, RAID 0/1/10/5. Integrated Intel PCIe host in processor for M.2 PCIe NVMe drives, optional RAID 0/1 with Intel NVMe RAID upgrade basic. Optional Broadcom 9440-8i, PCIe adapter, 12Gbps, SATA/SAS, RAID 0/1/10/5
5.25" flex bay	Two 5.25" flex bays, supports the following options: • Up to two half-height optical drives. • Up to two 5.25" slim ODD cages. • Up to two 5.25" slim ODD and HDD cages. • Up to one Front Access Storage Enclosure. • Up to one flex module for one or more of the following options: 9.0mm optical/ 15-in-1 USB 3.0 reader/front eSATA/front Thunderbolt/front USB 3.0 Type-C/ 4-digit diagnostic display *Note:* *1. Only one can be supported from 15-in-1 reader, Thunderbolt, and 4-digit display* *2. Up to two ports are suppported from 1394, eSATA, and USB Type-C*
Disk drive bays	Up to two internal 3.5" drive bays. Each bay supports one 3.5" or 2.5" disk. Up to two 2.5" or 3.5" SATA/SAS disk drives on 5.25" flex bays via 5.25" Front Access Storage Enclosure supports SATA or 5.25" slim ODD and HDD cage
M.2 slots	Up to 5 x M.2 PCIe NVMe SSD: • Two onboard M.2 slots. • Up to three PCIe 3.0 x4 adapters, each adapter supports one M.2 slot Supports RAID 0/1 on onboard M.2 disks, optional NVMe RAID upgrade is needed

Internal storage	
HDD 7.2K 3.5" SATA6Gbps	1TB/2TB/4TB
HDD 7.2K 2.5" SATA6Gbps	500GB FIPS
SSD 2.5" SATA6Gbps	256GB Opal/512GB/512GB Opal/1TB Opal/2TB Opal
M.2 PCIe NVMe, PCIe 3.0 x4	256GB Opal/512GB Opal/1TB Opal/2TB Opal

Media reader	9-in-1 USB 2.0 card reader on most models. Optional UHS-II 15-in-1 USB 3.0 reader on flex module
Network interfaces	Integrated one gigabit ethernet (Intel i219LM), supports Wake-on-LAN. Optional PCIe ethernet or wireless adapters are available
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant, switch to 1.2 via UEFI setting. Optional Kensington lock, and pad lock
Systems management	Intel Active Management Technology 11. ThinkStation Diagnostics for Windows. Optional front 4-digit diagnostic display on flex module
Base warranty	1 or 3-year limited onsite service with 9x5/NBD
HD Audio	Realtek ALC662 codec
Front ports	Two USB 3.0, microphone (3.5mm), headphone (3.5mm)
Rear ports	Two USB 2.0, four USB 3.0, one ethernet (RJ-45), three analog audio ports (line-in, line-out, mic-in), two PS/2

Components	Specification
Optional ports	Supports the following optional ports: • Optional COM port • Two USB Type-C ports via PCIe adapter, USB 3.1 gen 2. One 15W, one 5W • Two Thunderbolt ports (USB Type-C) on flex module, one of two ports supports video-out. • One eSATA on flex module • One internal USB 3.0 port
Power supply	One fixed 500W, autosensing, 92%, 80 PLUS Platinum qualified
Environmental specification	

Temperature - operating	50 °F to 95 °F (10 °C to 35 °C)
Temperature - non operating (no package)	14 °F to 140 °F (-10 °C to 60 °C)
Temperature - non operating (with package)	-40 °F to 140 °F (-40 °C to 60 °C)
Altitude - operating	(Unpressurized): -50ft-10000ft (-15.2m-3048m)
Humidity - operating	10%~80%, non-condensing
Humidity - storage (with package)	10%~90%, non-condensing

RoHS-compliant. GREENGUARD. EPEAT Gold rating and ENERGY STAR 6.1 qualified on following models:

Model	30BX0008US	30BX0009US
Processor	Intel Xeon W-2123	Intel Xeon W-2123
Memory	2x 8GB RDIMM DDR4-2666 ECC	2x 8GB RDIMM DDR4-2666 ECC
Disks	2x 1TB HDD 7.2K 3.5" SATA6Gbps	2x 256GB SSD 2.5" SATA6Gbps Opal
Graphics	NVIDIA Quadro P400 2GB	NVIDIA Quadro P4000 8GB
Optical	HH DVD±RW	HH DVD±RW
PSU	500W	500W
OS	Win10 Pro 64	Win10 Pro 64

ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/



Note: All expansion cards are optional

Expansion slots

Slot 1 (CPU)	PCIe 3.0 x16, full height, full length, 75W,
Slot 2 (CPU)	PCIe 3.0 x8, full height, full length, 25W, open ended
Slot 3 (CPU)	PCIe 3.0 x16, full height, full length, 75W
Slot 4 (PCH)	PCIe 3.0 x4, full height, half length, 25W, open ended

Note: When NVIDIA Quadro P5000, dual Quadro NVS 810, or dual Quadro P4000 is used, the HDD bay on the bottom will be unavailable

ThinkStation P520c